

View Online at <https://aerobasegroup.com/nsn/5320-01-232-5674>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.500 inches and 1.520 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.093 inches and 0.105 inches

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4360 inches and 0.4370 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.641 inches and 0.676 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.880 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

21000 pounds per square inch

**Hardness Rating:**

45.0 rockwell c and 48.0 rockwell c

**Thread Size:**

0.438 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate or cadmium

**Surface Treatment Specification:**

Mil-c-8837 type 2, class military specification 1st treatment response or nas 672 assn standard 2nd treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-c-8837 spec.