

View Online at <https://aerobasegroup.com/nsn/5320-01-232-7010>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.911 inches and 0.951 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.127 inches and 0.130 inches

Shank Diameter:

Between 0.327 inches and 0.328 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.456 inches and 0.492 inches

Grip Length:

Between 0.439 inches and 0.500 inches

Thread Size:

0.312 inches

Shear Strength:

156000 single pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Oversize restricted to repair work, t.O. 1f-16-1299

Material:

Steel comp h11

Material Specification:

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

Surface Treatment:

Cadmium and nickel

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas4452 manufacturers standard and 80205-nas4444 manufacturers specification

Specification Or Standard:

2 type and 1 class and h composition

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0