## NSN 5320-01-234-3156

Pin-rivet - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5320-01-234-3156



## 3a **Thread Direction: Right-hand Identification Code Color:** Blue **Fastener Length:** Between 0.877 inches and 0.897 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches Shank Diameter: Between 0.2016 inches and 0.2026 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: 0.567 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.190 inches Shear Strength: 95000 single pounds per square inch **Special Features:** Color top of head only Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response Surface Treatment: Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

## NSN 5320-01-234-3156

Pin-rivet - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

