## NSN 5320-01-234-3156

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-234-3156

view Online at https://aerobasegroup.com/nsi//3320-01-234-3130
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Blue
Fastener Length:
Between 0.877 inches and 0.897 inches
Head Style:
Err-090
Head Height:
Between 0.064 inches and 0.074 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.2016 inches and 0.2026 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.357 inches and 0.377 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
0.567 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.190 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Color top of head only
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response or ams 5731 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

## NSN 5320-01-234-3156

Pin-rivet - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A528u0