NSN 5320-01-234-9480

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-234-9480
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.892 inches and 1.922 inches
Head Style:
Err-090
Head Height:
Between 0.078 inches and 0.088 inches
Width Between Flats:
Between 0.1875 inches and 0.1895 inches
Shank Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Grip Length:
Between 1.428 inches and 1.448 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
260000 pounds per square inch
Thread Size:
0.3750 inches
Shear Strength:
156000 single pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1326 professional/industrial association standard
Shelf Life:

N/a

NSN 5320-01-234-9480

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0