# NSN 5320-01-235-1227

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-235-1227



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.010 inches and 1.030 inches

## Head Style:

Flush countersunk

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

#### Shank Diameter:

Between 0.2490 inches and 0.2495 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.387 inches and 0.412 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

### Grip Length:

0.630 inches

# Thready Qty Per Inch (tpi):

28

# Thread Size:

0.250 inches

### Shear Strength:

125000 single pounds per square inch

#### **Special Features:**

Head color white.

### Material:

Steel comp xm-13

### **Material Specification:**

Ams 5629 assn standard single material response

#### Surface Treatment:

Paint head

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-235-1227

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

