

View Online at <https://aerobasegroup.com/nsn/5320-01-235-4635>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.052 inches and 1.072 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.6335 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.567 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488, type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-83488 spec.