NSN 5320-01-236-2621

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-236-2621

| Fastener Length: |
|---|
| 0.388 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.172 inches and 0.176 inches |
| Head Major Diameter: |
| Between 0.282 inches and 0.290 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.188 inches and 0.250 inches |
| Min. Tensile Strength (psi): |
| 1050 pounds per square inch |
| Shear Strength: |
| 1665 single pounds per square inch |
| Countersink Angle: |
| 108.0 degrees |
| Special Features: |
| Stem color yellow |
| Material: |
| Iron alloy 660 stem |
| Material Specification: |
| Qq-n-281 federal specification single material response sleeve |
| Surface Treatment: |
| Passivate stem |
| Surface Treatment Specification: |
| Qq-p-416, ty ii, cl 3 federal specification single treatment response sleeve or nas 4006 assn standard single treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| |