NSN 5320-01-237-5767

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-237-5767

Fastener Length:

0.263 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.172 inches and 0.176 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

Between 0.282 inches and 0.290 inches

Expansion Device:

Serrated stem-type w

End Application:

W/s: joint stars target radar system

Grip Length:

Between 0.101 inches and 0.125 inches

Min. Tensile Strength (psi):

1050 pounds per square inch

Shear Strength:

1665 single pounds per square inch

Countersink Angle:

108.0 degrees

Special Features:

Stem color yellow

Material:

Iron alloy 660 stem

Material Specification:

Qq-n-281 federal specification single material response sleeve

Surface Treatment:

Passivate stem

Surface Treatment Specification:

Qq-p-416, ty ii, cl 3 federal specification single treatment response sleeve or nas 4006 assn standard single treatment response sleeve

```
Shelf Life:
```

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0