## NSN 5320-01-237-9403

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-237-9403

view Online at https://aerobasegroup.com/nsn/5320-01-237-9403
Thread Class:
3b
Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.465 inches and 0.468 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.528 inches
Expansion Device:
Expander
Grip Length:
0.500 inches
Thready Qty Per Inch (tpi):
24
Thread Size:
0.312 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Special Features:
Furnished without bolt
Heat Treatment:
Annealed sleeve
Material:
Steel comp 305 sleeve or steel comp 302 sleeve or steel comp xm-7 sleeve
Material Specification:
Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or astm a493
assn standard 3rd material response sleeve
Surface Treatment:
Cadmium expander
Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response expander
Thread Series Designator:
Jnjf
Shelf Life:
N/a
Init Of Measure:

--

## NSN 5320-01-237-9403

Blind Rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A040a0