NSN 5320-01-237-9406

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-237-9406 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.115 inches and 1.135 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1330 inches and 0.1350 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** 0.138-32 unjc-3b threaded hole 0.300 in. Min 0.345 in. Maximum deep; slot 0.120 in. Lg 0.060 in. W 0.350 in. From head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:**

N/a

Unjf

Shelf Life:

NSN 5320-01-237-9406

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0