## NSN 5320-01-237-9794

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-237-9794 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.043 inches and 1.063 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2540 inches and 0.2545 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.3948 inches Lubrication: Solid film no. 905, hi shear corporation and cetyl alcohol **Grip Length:** 0.438 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3 fscm 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-237-9794

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0