# NSN 5320-01-237-9953

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-237-9953



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.375 inches and 1.395 inches

## Head Style:

Err-090

## Width Between Flats:

Between 0.1895 inches and 0.1930 inches

## Shank Diameter:

Between 0.4365 inches and 0.4370 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

0.8884 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corporation and solid film

## Grip Length:

0.755 inches

# Thready Qty Per Inch (tpi):

20

## **Thread Size:**

0.438 inches

## Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

## Material Specification:

Ams 5629 assn standard single material response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-237-9953

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

