
# NSN 5320-01-238-0682

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Black

#### Fastener Length:

Between 1.127 inches and 1.147 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.3016 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.817 inches

#### Thready Qty Per Inch (tpi):

32

#### **Thread Size:**

0.190 inches

## Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### **Special Features:**

Color on thread end

#### Material:

Titanium alloy uns r56400

#### Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

### Surface Treatment:

Aluminum

### Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

# NSN 5320-01-238-0682

Pin-rivet - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

