

View Online at <https://aerobasegroup.com/nsn/5320-01-238-1546>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.597 inches and 1.617 inches

Head Style:

Countersunk w/reverse chamfer

Head Height:

Between 0.1363 inches and 0.1433 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3271 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

0.6335 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.067 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

210000 pounds per square inch

Hardness Rating:

44.0 rockwell c and 50.0 rockwell c

Thread Size:

0.312 inches

Countersink Angle:

100.0 degrees

Special Features:

6-32unj-3b threaded hole from head 0.300 in. Min 0.345 in. Maximum deep; 0.120 in. Slot 0.650 in. From head

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0