

View Online at <https://aerobasegroup.com/nsn/5320-01-239-5948>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 0.806 inches and 0.833 inches

**Head Style:**

Flush countersunk

**Shank Diameter:**

0.3260 inches

**Shank Style:**

Pin-riquet, tapered, threaded

**Head Major Diameter:**

0.494 inches

**Tip Diameter:**

0.3202 inches

**Lubrication:**

Dry film and cetyl alcohol

**Grip Length:**

0.442 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.312 inches

**Shear Strength:**

125000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Injection port 8-32 unjc-3b thread; depth 0.300-0.345 in. Or to the bottom of the port

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0