

View Online at <https://aerobasegroup.com/nsn/5320-01-240-4157>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

0.4370 inches

**Head Style:**

Flush countersunk

**Hole Diameter:**

Between 0.0791 inches and 0.0801 inches

**Shoulder Diameter:**

Between 0.1630 inches and 0.1635 inches

**Shoulder Length:**

Between 0.1590 inches and 0.1710 inches

**Shank Diameter:**

Between 0.1570 inches and 0.1595 inches

**Shank Style:**

**Head Major Diameter:**

Between 0.2564 inches and 0.2612 inches

**Hole Depth:**

Between 0.115 inches and 0.135 inches

**Grip Length:**

0.1250 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Material:**

Iron alloy 660

**Material Specification:**

Ams5737 assn standard single material response or ams5731 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Hi-shear 258 mfr ref single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0