NSN 5320-01-240-6439

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-240-6439 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.597 inches and 1.617 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1298 inches and 0.1368 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3427 inches and 0.3432 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.6335 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.067 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** 6-32unjc-3b threaded hole from head 0.300 in. Min 0.345 in. Maximum deep; 0.120 in. Slot 0.650 in. From head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5320-01-240-6439

Pin-rivet - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A528u0