

View Online at <https://aerobasegroup.com/nsn/5320-01-240-8095>

**Fastener Length:**

0.385 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.124 inches and 0.128 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.221 inches and 0.229 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Min. Tensile Strength (psi):**

675 pounds per square inch

**Shear Strength:**

1020 single pounds per square inch

**Countersink Angle:**

Between 98.5 degrees and 101.5 degrees

**Special Features:**

Single action

**Material:**

Stainless steel stem

**Material Specification:**

Qq-n-281 federal specification single material response sleeve

**Surface Treatment:**

Passivate stem

**Surface Treatment Specification:**

Qq-p-416, ty ii, cl 3 federal specification single treatment response sleeve or nas4006 assn standard single treatment response sleeve

**Specification Data:**

80205-nas1921 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0