## NSN 5320-01-241-1578

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-241-1578 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.635 inches and 1.655 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1070 inches and 0.1095 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and dry film **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Injection hole 0.120 in. Lg, located 0.870 in. Min. 0.875 in. Maximum from top of head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5320-01-241-1578

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0