# NSN 5320-01-241-2831

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-241-2831



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.115 inches and 1.135 inches

### Head Style:

Err-090

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

### Shank Diameter:

Between 0.3115 inches and 0.3120 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

0.6335 inches

#### Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

0.630 inches

# Thready Qty Per Inch (tpi):

24

# Thread Size:

0.312 inches

# Shear Strength:

125000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

# **Special Features:**

White paint on head

#### Material:

Steel comp xm-13

# Material Specification:

Ams 5629 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-241-2831

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

