
NSN 5320-01-241-6481

Pin-rivet - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand** Fastener Length: Between 1.410 inches and 1.430 inches **Head Style:** Countersunk w/reverse chamfer **Head Height:** Between 0.1363 inches and 0.1433 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3271 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: 0.6335 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp Grip Length: 0.880 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 210000 pounds per square inch Hardness Rating: 44.0 rockwell c and 50.0 rockwell c **Thread Size:** 0.312 inches **Countersink Angle:** 100.0 degrees **Special Features:** 6-32unjc-3b threaded hole from head 0.300 in. Min 0.345 in. Maximum deep; 0.120 in. Slot 0.470 in. From head Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5320-01-241-6481

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

