NSN 5320-01-242-0784

Blind Rivet - Page 1 of 1

A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-242-0784

| view Offilite at https://aerobasegroup.com/hsh/5525-01-242-0704 |
|--|
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.092 inches and 0.097 inches |
| Shank Style: |
| Self-plugging high clinch shank |
| Head Major Diameter: |
| 0.148 inches |
| Expansion Device: |
| Serrated stem-type w |
| Grip Length: |
| Between 0.126 inches and 0.187 inches |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Rust preventive oil base finish for stem |
| Heat Treatment: |
| Annealed sleeve |
| Material: |
| Steel comp 1018 sleeve |
| Surface Treatment: |
| Cadmium sleeve and chromate sleeve |
| Surface Treatment Specification: |
| Qq-p-416 type 2 cl 2 federal specification single treatment response sleeve |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |