NSN 5320-01-242-4360

Pin-rivet - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-242-4360 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.925 inches and 0.945 inches **Head Style:** Err-090 **Head Height:** Between 0.170 inches and 0.180 inches Width Between Flats: Between 0.269 inches and 0.289 inches **Shank Diameter:** Between 0.4985 inches and 0.4995 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **End Application:** W/s: joint stars target radar system; aircraft, starlifter c-141 **Grip Length:** 0.255 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Heat Treatment:** T-6 solution heat treated Material: Aluminum alloy 7075 **Material Specification:** Qq-a-225/9 federal specification single material response or qq-a-430 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Thread Series Designator:** Unjf

NSN 5320-01-242-4360

Pin-rivet - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-a-8625 spec.