NSN 5320-01-242-7028

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-242-7028

Graen Fastener Length: 0.303 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp 4540 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp Material Specification: Astm a331 asan standard single material response Surface Treatment: Cadhium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shaft Lite: No Unit Of Measure: — Demilitarization: No Piffig: A04000	Identification Code Color:
0.303 inches Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8815 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qup-416 type 2, cl 2 federal specification single treatment response sleeve Sheff Life: N/a Unit Of Measure: Demilitarization: No Flig:	Green
Head Style: Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 asan standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Fastener Length:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification single treatment response sleeve Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	0.303 inches
Shank Slameter: Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stern Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Head Style:
Between 0.197 inches and 0.199 inches Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: Hardness Rating: 112000 single pounds per square inch Countersink Angle: Between 9.9 0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Style: Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8616 or steel comp 8640 or steel comp 8740 Material Specification: Astem a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure:	Shank Diameter:
Self-plugging mechanically locked stem Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Sheft Life: N/a Unit Of Measure: — Demilitarization: No Fig:	Between 0.197 inches and 0.199 inches
Head Major Diameter: 0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Shank Style:
0.386 inches Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qcp-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Self-plugging mechanically locked stem
Expansion Device: Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Head Major Diameter:
Serrated stem-type w Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material: Steel specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	0.386 inches
Grip Length: Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Expansion Device:
Between 0.120 inches and 0.157 inches Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	Serrated stem-type w
Hardness Rating: 48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Grip Length:
48.0 rockwell c stem and 53.0 rockwell c stem Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.120 inches and 0.157 inches
Shear Strength: 112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hardness Rating:
112000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	48.0 rockwell c stem and 53.0 rockwell c stem
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Shear Strength:
Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	112000 single pounds per square inch
Material: Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Countersink Angle:
Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 99.0 degrees and 101.0 degrees
4815 or steel comp 8615 or steel comp 8640 or steel comp 8740 Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Material Specification: Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp
Astm a331 assn standard single material response Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	4815 or steel comp 8615 or steel comp 8640 or steel comp 8740
Surface Treatment: Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:
Cadmium stem Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Astm a331 assn standard single material response
Surface Treatment Specification: Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cadmium stem
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
N/a Unit Of Measure: Demilitarization: No Fiig:	Qq-p-416 type 2, cl 2 federal specification single treatment response sleeve
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	Demilitarization:
	No
A040a0	Fiig:
	A040a0