## NSN 5320-01-242-9953

Blind Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-242-9953

## **Thread Class:** 3a **Thread Direction: Right-hand** Fastener Length: 0.858 inches **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) Shank Diameter: Between 0.387 inches and 0.390 inches Shank Style: Blind rivet, nut and bolt (assembly) Head Major Diameter: Between 0.7556 inches and 0.7604 inches **Expansion Device:** Expander Lubrication: Cetyl alcohol Grip Length: Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches Shear Strength: 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp 305 sleeve **Material Specification:** Qq-s-763 federal specification single material response sleeve Surface Treatment: Passivate bolt Surface Treatment Specification: Qq-p-416, type 1, cl 2 federal specification single treatment response sleeve **Thread Series Designator:** Unjf Shelf Life: N/a Unit Of Measure:

---

## NSN 5320-01-242-9953

Blind Rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A040a0

