## NSN 5320-01-243-2939

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-243-2939 Fastener Length: 0.5735 inches **Head Style:** Hexagon **Head Height:** 0.113 inches **Shank Diameter:** Between 0.2280 inches and 0.2300 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Threaded stem **Grip Length:** Between 0.470 inches and 0.531 inches Width Across Flats: Between 0.305 inches and 0.312 inches Min. Tensile Strength (psi): 1400 pounds per square inch **Shear Strength:** 5240 double pounds per square inch Material: Steel comp 4130 body or steel comp 4140 body or steel comp 8740 body **Material Specification:** Qq-s-763 federal specification all material responses sleeve or ams 5639 assn standard all material responses sleeve or ams 5641 assn standard all material responses sleeve **Surface Treatment:** Passivate sleeve and cadmium sleeve **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response stem Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.