NSN 5320-01-243-9476

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-243-9476 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.165 inches and 1.185 inches **Head Style:** Err-090 **Head Height:** Between 0.068 inches and 0.078 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3110 inches and 0.3120 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.475 inches and 0.505 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.630 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 45.0 rockwell c and 48.0 rockwell c **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-I-8837, type 2, cl 2 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-243-9476

Pin-rivet - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-I-8837 spec.