## NSN 5320-01-244-2349

Blind Rivet - Page 1 of 2

3b



View Online at https://aerobasegroup.com/nsn/5320-01-244-2349

Thread Class:

Thread Direction:
Right-hand
Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.309 inches and 0.312 inches
Shank Style:
Blind rivet, nut and bolt (assembly)
Head Major Diameter:
0.024 inches
Expansion Device:
Expander
Lubrication:
Solid film
Grip Length:
Between 0.188 inches and 0.250 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
125000 single pounds per square inch
Countersink Angle:
Between 98.0 degrees and 102.0 degrees
Material:
Steel comp 304 sleeve or steel comp 305 sleeve
Material Specification:
Qq-s-763 cond a federal specification all material responses sleeve
Surface Treatment:
Passivate sleeve
Surface Treatment Specification:
Qq-p-35, type 1 federal specification single treatment response sleeve
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5320-01-244-2349

Blind Rivet - Page 2 of 2



Fiig:

A040a0