

View Online at <https://aerobasegroup.com/nsn/5320-01-246-1060>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.160 inches and 1.180 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.078 inches and 0.088 inches

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.565 inches and 0.600 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**End Application:**

C-5 aircraft

**Grip Length:**

0.630 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

45.0 rockwell c and 48.0 rockwell c

**Thread Size:**

0.375 inches

**Shear Strength:**

125000 single pounds per square inch

**Material:**

Steel comp h11

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Mil-c-8837, type 2 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0

**Mil-std (military Standard):**

Mil-c-8837 spec.