NSN 5320-01-246-1060

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-246-1060
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.160 inches and 1.180 inches
Head Style:
Err-090
Head Height:
Between 0.078 inches and 0.088 inches
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
End Application:
C-5 aircraft
Grip Length:
0.630 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
45.0 rockwell c and 48.0 rockwell c
Thread Size:
0.375 inches
Shear Strength:
125000 single pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Mil-c-8837, type 2 military specification single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-246-1060

Pin-rivet - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A528u0

Mil-std (military Standard):

Mil-c-8837 spec.