# NSN 5320-01-246-1066

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-246-1066



### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 1.177 inches and 1.197 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.037 inches and 0.047 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0801 inches

#### Shank Diameter:

Between 0.1625 inches and 0.1635 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.242 inches and 0.262 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

### Grip Length:

0.880 inches

#### Thready Qty Per Inch (tpi):

32

#### Hardness Rating:

45.0 rockwell c and 48.0 rockwell c

#### **Thread Size:**

0.164 inches

#### Shear Strength:

125000 single pounds per square inch

#### Material:

Steel comp h11

#### Material Specification:

Ams 6487 assn standard single material response

#### Surface Treatment:

Cadmium and chromate

# Surface Treatment Specification:

Mil-c-8837, type 2 cl 2 military specification single treatment response

# Thread Series Designator:

Unjc

### Shelf Life:

N/a

# NSN 5320-01-246-1066

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-c-8837 spec.

