NSN 5320-01-246-1839

Pin-rivet - Page 1 of 2





Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.823 inches and 0.843 inches

Head Style:

Err-090

Head Height:

Between 0.059 inches and 0.069 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.387 inches and 0.412 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

End Application:

Aircraft, eagle f-15; aircraft, tomcat f-14; aircraft, harrier av-8b; aircraft, sof (ac-130h, mc-130h, ec-130e, hc-130); aircraftgalaxy c-5; aircraft, b-1b

ancian, b-ib

Grip Length:

0.443 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-246-1839

Pin-rivet - Page 2 of 2

Fiig: A528u0

