NSN 5320-01-246-3936

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-246-3936 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.397 inches and 1.417 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3956 inches and 0.3961 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5604 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.572 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Tiodize type 2, cagec 73197 mfr ref single treatment response or ti fin 400, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-246-3936

Pin-rivet - Page 2 of 2



Demi			

No

Fiig:

A528u0