NSN 5320-01-246-8375

Pin-rivet - Page 1 of 2

Thread Class:

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5320-01-246-8375

| Tillead Direction. | | | | | |
|--|--|--|--|--|--|
| Right-hand | | | | | |
| Identification Code Color: | | | | | |
| Green | | | | | |
| Fastener Length: | | | | | |
| Between 1.323 inches and 1.343 inches | | | | | |
| Head Style: | | | | | |
| Err-090 | | | | | |
| Head Height: | | | | | |
| Between 0.059 inches and 0.069 inches | | | | | |
| Width Between Flats: | | | | | |
| Between 0.095 inches and 0.097 inches | | | | | |
| Shank Diameter: | | | | | |
| Between 0.249 inches and 0.250 inches | | | | | |
| Shank Style: | | | | | |
| Pin-rivet, straight, threaded | | | | | |
| Head Major Diameter: | | | | | |
| Between 0.387 inches and 0.412 inches | | | | | |
| Lubrication: | | | | | |
| Cetyl alcohol | | | | | |
| Grip Length: | | | | | |
| Between 0.933 inches and 0.943 inches | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 28 | | | | | |
| Thread Size: | | | | | |
| 0.250 inches | | | | | |
| Shear Strength: | | | | | |
| 9300 double pounds per square inch | | | | | |
| Special Features: | | | | | |
| Color code green on threads | | | | | |
| Material: | | | | | |
| Iron alloy 660 | | | | | |
| Material Specification: | | | | | |
| Ams5737 assn standard 1st material response or ams5731 assn standard 2nd material response | | | | | |
| Surface Treatment: | | | | | |
| Cadmium | | | | | |
| Surface Treatment Specification: | | | | | |
| Qq-p-416, type ii, class 3 federal specification single treatment response | | | | | |
| Thread Series Designator: | | | | | |
| Unjf | | | | | |
| | | | | | |

NSN 5320-01-246-8375

Pin-rivet - Page 2 of 2



| _ | | | | |
|---|-----|------|---|------|
| c | hο | JIF. | | ife: |
| J | 116 | | _ | HG. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0