

View Online at <https://aerobasegroup.com/nsn/5320-01-246-9829>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Fastener Length:**

Between 0.489 inches and 0.509 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.079 inches and 0.080 inches

**Shank Diameter:**

Between 0.162 inches and 0.163 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.325 inches and 0.330 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.182 inches and 0.192 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.164 inches

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Qq-p-416, type 1, cl 2 assn standard single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unjc

**Specification Data:**

73197-hl65 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0