NSN 5320-01-246-9829

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-246-9829 **Thread Class:** За **Thread Direction:** Left-hand Fastener Length: Between 0.489 inches and 0.509 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.079 inches and 0.080 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.325 inches and 0.330 inches Lubrication: Cetyl alcohol **Grip Length:** Between 0.182 inches and 0.192 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.164 inches **Countersink Angle:** 100.0 degrees Material: Titanium alloy **Material Specification:** Qq-p-416, type 1, cl 2 assn standard single material response **Surface Treatment:** Cadmium **Thread Series Designator:** Unjc **Specification Data:** 73197-hl65 professional/industrial association standard Shelf Life:

Unit Of Measure:

N/a

NSN 5320-01-246-9829

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0