

View Online at <https://aerobasegroup.com/nsn/5320-01-247-1701>

**Fastener Length:**

1.285 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2890 inches and 0.2910 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.453 inches and 0.503 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.532 inches and 0.594 inches

**Min. Tensile Strength (psi):**

3650 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Shear Strength:**

11800 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp h11 stem

**Material Specification:**

Ams5667 assn standard single material response sleeve or ams5582 assn standard single material response sleeve or ams5731 assn standard single material response sleeve or ams5732 assn standard 4th material response sleeve or ams5737 assn standard 5th material response sleeve

**Surface Treatment:**

Cadmium stem and chromate stem

**Surface Treatment Specification:**

Nas672 assn standard 1st treatment response stem and qq-p-416 federal specification 2nd treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0