

View Online at <https://aerobasegroup.com/nsn/5320-01-247-2788>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.335 inches and 1.355 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1582 inches and 0.1617 inches

Shank Diameter:

Between 0.4112 inches and 0.4117 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.5916 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.510 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Tiodize type 2, caged 73197 mfr ref single treatment response or ti-fin 400, caged 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0