NSN 5320-01-247-2789

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-247-2789 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.533 inches and 1.553 inches **Head Style:** Err-090 **Head Height:** Between 0.103 inches and 0.116 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.5372 inches and 0.5377 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.735 inches and 0.770 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 0.698 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.500 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Tiodize type 2, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-247-2789

Pin-rivet - Page 2 of 2



| Demi | | | |
|------|--|--|--|
| | | | |
| | | | |

No

Fiig:

A528u0