NSN 5320-01-247-2790

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-247-2790 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.118 inches and 1.138 inches **Head Style:** Err-090 **Head Height:** Between 0.078 inches and 0.088 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.4112 inches and 0.4117 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.565 inches and 0.600 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 0.448 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Tiodize, type 2, cagec 73197 mfr ref single treatment response or ti fin 400, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-247-2790

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0