# NSN 5320-01-247-6890

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-247-6890



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.123 inches and 1.143 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.045 inches and 0.055 inches

## Width Between Flats:

Between 0.0791 inches and 0.0806 inches

## Shank Diameter:

Between 0.2250 inches and 0.2255 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.295 inches and 0.315 inches

## Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.698 inches

## Thready Qty Per Inch (tpi):

32

## Thread Size:

0.190 inches

## Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy uns r56400

## Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Ti-shield 3, cagec 73197 mfr ref single treatment response or tiodize type 2 cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5320-01-247-6890

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

