## NSN 5320-01-247-6892

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-247-6892 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.242 inches and 1.262 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.5554 inches and 0.5604 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** 0.5604 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corporation and solid film **Grip Length:** 0.572 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ti-shield 3, cagec 73197 mfr ref single treatment response or tiodize type 2, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-247-6892

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0