

View Online at <https://aerobasegroup.com/nsn/5320-01-247-7620>

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2890 inches and 0.2910 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.499 inches and 0.507 inches

Expansion Device:

Threaded sleeve

Grip Length:

Between 0.595 inches and 0.656 inches

Min. Tensile Strength (psi):

3650 pounds per square inch

Hardness Rating:

48.0 rockwell c stem and 53.0 rockwell c stem

Shear Strength:

11800 double pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp h11 stem

Material Specification:

Ams5667 assn standard single material response sleeve or ams5582 assn standard single material response sleeve or ams5731 assn standard single material response sleeve or ams5732 assn standard 1st material response sleeve or ams5737 assn standard 2nd material response sleeve

Surface Treatment:

Cadmium stem and chromate stem

Surface Treatment Specification:

Nas672 assn standard 1st treatment response stem and qq-p-416 federal specification 2nd treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0