# NSN 5320-01-247-9035

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-247-9035

# Fastener Length:

Between 0.490 inches and 0.510 inches

# Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.006 inches

# Shank Diameter:

Between 0.186 inches and 0.189 inches

#### Shank Style:

Straight w/radius chamfered tip

## Head Major Diameter:

0.3016 inches

## Head Minor Diameter:

0.198 mils and 0.208 centimeters

## **Countersink Height:**

0.046 inches

## Shear Strength:

41000 single pounds per square inch

# **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

# Heat Treatment:

T-73 solution heat treated

## Material:

Aluminum alloy

# **Material Specification:**

Qq-a-430, comp 7050 federal specification single material response

# Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A040a0

# Mil-std (military Standard):

Mil-a-8625 spec.