## NSN 5320-01-248-3304

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-248-3304 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.830 inches and 1.850 inches **Head Style:** Err-090 Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3896 inches and 0.3901 inches **Shank Style: Head Major Diameter:** 0.7604 inches Lubrication: Solid film and cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.255 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.375 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a **Unit Of Measure:** 

## NSN 5320-01-248-3304

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0