NSN 5320-01-249-0510

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-249-0510



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.058 inches and 1.083 inches

Head Style:

Flush countersunk

Shank Diameter:

0.3260 inches

Shank Style:

Pin-rivet, tapered, threaded

Head Major Diameter:

0.494 inches

Tip Diameter:

0.3150 inches

Lubrication:

Dry film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.692 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

One oblong hole 0.120 in. Lg, 0.1015 in. from top of head, thd hole through longitudinal centerline of head 8-32unjc-3b

Material:

Stainless steel

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-249-0510

Pin-rivet - Page 2 of 2

Fiig: A528u0

