

View Online at <https://aerobasegroup.com/nsn/5320-01-249-4281>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.145 inches and 1.165 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2696 inches and 0.2701 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

0.3948 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.510 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

100.0 degrees

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Tiodize type 2, cagec 73197 mfr ref single treatment response or ti fin 400, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0