

View Online at <https://aerobasegroup.com/nsn/5320-01-249-9531>

**Fastener Length:**

0.694 inches

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.310 inches and 0.312 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

0.634 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.406 inches and 0.470 inches

**Min. Tensile Strength (psi):**

112000 pounds per square inch

**Hardness Rating:**

48.0 rockwell c stem and 53.0 rockwell c stem

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

"u" denotes single action fasteners installed with a single action tool

**Material:**

Steel comp e4340 or steel comp 4027 or steel comp 4037 or steel comp 4130 or steel comp 4140 or steel comp 4150 or steel comp 4340 or steel comp 4620 or steel comp 4815 or steel comp 6150 or steel comp 8615 or steel comp 8620 or steel comp 8630 or steel comp 8640 or steel comp 8740

**Material Specification:**

Astm a331 assn standard single material response

**Surface Treatment:**

Cadmium stem

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0