# NSN 5320-01-249-9672

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-249-9672

# Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

# Shank Diameter:

Between 0.3110 inches and 0.3120 inches

# Shank Style:

Self-plugging high clinch shank

# Head Major Diameter:

0.558 inches

#### **Expansion Device:**

Expander

#### Lubrication:

Wax or dry film or grease film

#### Grip Length:

Between 1.406 inches and 1.469 inches

#### **Countersink Angle:**

60.0 degrees

### **Special Features:**

Protrusion from head

#### Heat Treatment:

Annealed sleeve

# Material:

Steel comp 4130 nut or steel comp 8740 nut or steel comp 4140 nut

## Material Specification:

Ams 5641 assn standard 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve

## Surface Treatment:

Cadmium sleeve

## Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response nut

#### Shelf Life:

N/a

# Unit Of Measure:

```
---
```

#### Demilitarization:

No

# Fiig:

A040a0

# Mil-std (military Standard):

Mil-s-6758 spec.